

ASPHALT MATERIAL

ASPHALT BIO 50

Potmix® Asphalt Bio 50 is a climate friendly, high-performance asphalt for durable and permanent repairs of asphalt surfaces. Its binder is a unique blend of bitumen and bio-oil. The product cures under pressure and in contact with moisture. Watering it before compaction quickens the curing process — consumption approx. 2 l water per 20 kg material. Traffic can be immediately let onto the repaired area. Asphalt Bio 50 works equally well in both summer and winter season, and is completely VOC/solvent free. It is to be stored in dry conditions.



- **CONTAINS LESS THAN HALF THE BITUMEN OF REGULAR ASPHALT**
- **QUICK CURING TO 5 kN IN 48 h**
- **CURES UNDER COMPACTION AND IN CONTACT WITH WATER**

User instructions: prepare the repair area by removing debris and fill a base course of compacted sand or gravel. Leave a depth of 1-4 cm for the asphalt — for deeper areas the asphalt should be compacted in layers. Use Potmix® Asphalt Primer for extra adhesion on smooth and difficult to attach surfaces. Fill the repair area with the asphalt and apply water to it. Compress thereafter the asphalt with intermittent pressure. If no compacting tools are available, traffic can be brought onto the surface to apply the compacting force.

Article no.	Size	Unit	Units / pallet
11055	20 kg	bag	40
11057	20 kg	bucket	44
11059	1 250 kg	big bag	1

